




# ASSEMBLY INSTRUCTION


## HTX | Hand tool for tightening the bushing of the XLR X, XX and etherCON NE8MX series



Tool for the bushing of XLR X & etherCON NE8MX\* series

Tool for the bushing of XLR XX series

### ASSEMBLY INSTRUCTION



- (A)** Slide the cable through the slot.
- (B)** Position the plug onto the tool.
- (C)** Press the connector with the bushing onto the tool and tighten the bushing with **max. torque 3 Nm (2.2 lb-ft).tight.**

Neutrik AG	LI	T: +423 / 237 24 24	F: +423 / 232 53 93	Neutrik France	FR	T: +33 1 / 4131 6750	F: +33 1 / 4131 0511
Neutrik USA Inc.	USA	T: +1 704 / 972 3050	F: +1 704 / 438 9202	Neutrik Tokyo Ltd.	JP	T: +81 3 / 3663 4733	F: +81 3 / 3663 4796
Neutrik (UK) Ltd.	UK	T: +44 1983 / 811 441	F: +44 1983 / 811 439	Neutrik Hong Kong Ltd.	HK	T: +852 / 2687 6055	F: +852 / 2687 6052
Neutrik Vertriebs GmbH	DE/NL/AT/DK	T: +49 8131 / 280 890	F: +49 8131 / 280 830	Neutrik India Pvt. Ltd.	IND	T: +91 / 982 05 43 424	F: +91 / 22 26163 540

Draft. Nr.: BDA 578 | Update: 2019-09-02 | Data subject to change without prior notice. © 2019 NEUTRIK®. NEUTRIK® are registered trademark of NEUTRI AG. ALL RIGHTS RESERVED.