



NC3MP-BAG

3 pole male receptacle, solder contacts, black metal housing, silver contacts

Smallest available traditional style metal panel mount connector with large solder cups for ease hard wiring.

Features & Benefits

- Smallest available hard wiring receptacles with large solder cups
- Compatible with switchcraft D*M, D*F; Cannon XLB2*31, XLB2*32

Technical Information

| Product | |
|-----------------|-----------|
| Title | NC3MP-BAG |
| Connection Type | XLR |
| Gender | male |

| Electrical | |
|------------------------------|---------------------------------|
| Capacitance between contacts | $\leq 4\text{ pF}$ |
| Contact resistance | $\leq 5\text{ m}\Omega$ |
| Dielectric strength | 1,5 kVdc |
| Insulation resistance | $> 10\text{ G}\Omega$ (initial) |
| Rated current per contact | 16 A |
| Rated voltage | $< 50\text{ V}$ |

| Mechanical | |
|--------------------|------------------------|
| Insertion force | $\leq 20\text{ N}$ |
| Withdrawal force | $\leq 20\text{ N}$ |
| Lifetime | > 1000 mating cycles |
| Wiresize | |
| Wiring | Solder contacts |
| Locking device | Latch lock |
| Mounting direction | Front mounting |
| Chassis shape | P |

| Material | |
|-----------------|----------------------------|
| Contact plating | 2 µm Ag over 2 µm Ni |
| Contacts | Brass (CuZn35Pb2) |
| Insert | Polyamide (PA 6.6 30 % GR) |
| Locking element | Steel Ck67 |
| Shell | Zinc diecast (ZnAl4Cu1) |
| Shell plating | Black chromium |

| Environmental | |
|---------------------|---------------------------|
| Flammability | UL 94 HB |
| Standard compliance | IEC 61076-2-103 |
| Protection class | IP 40 |
| Solderability | Complies with IEC 68-2-20 |
| Temperature range | -30 °C to +80 °C |