

## NAC3FX-W-TOP-L

### PHASE OUT

direct replacement / successor: NAC3F-TRUE1-L



Locking female cable connector for big power cord diameters 10–16 mm (0.39–0.63 inches) such as H07RN-F3G2.5 or SOOW 12/3 / SOOW 14/3.

Certified to EN/UL 60320-1.

Power out, screw terminals, IP65, up to 16 A (USA: 20A)

The powerCON TRUE1 TOP is a single phase connector for outdoor applications with breaking capacity (CBC), i.e. it can be connected or disconnected under load or live.





## Features & Benefits

- ✓ For cable diameters 10-16 mm (0.39 – 0.63 inches)
- ✓ IEC EN 60320-1 and UL 60320-1 certified, thus accepted as a component for cord sets acc. to IEC 60799 and of equipment acc. to IEC 62368-1
- ✓ Heavy duty sealed power connector for harsh and demanding environment
- ✓ TOP True Outdoor Protection
- ✓ Uses high impact UV-resistant materials
- ✓ Single phase connector with Circuit Breaking Capability (20 A 250 VAC)
- ✓ Extremely robust and reliable cable retention
- ✓ Superior NEUTRIK quality standard

## Product related questions and answers

Question	Answer
Is the new cable entry patented?	There is a patent application in process which is related to the cable entry section.

How are the certifications different to the current version NAC3*X-W-TOP?	<p>EN certification:</p> <p>Both versions are certified according to EN 60320-1.</p> <p>The new L-version however is certified for large cables as follows:</p> <p>H07RN-F 3G 2,5 mm<sup>2</sup></p> <p>The old version is certified for cable types:</p> <p>H07RN-F 3G 1,5 mm<sup>2</sup> and H05VV-F 3G 1,0 - 2,5 mm<sup>2</sup></p> <p>UL certification:</p> <p>The new L-version is certified according to UL 60320-1 for cables SOOW 12/3 and SOOW 14/3. The old version is certified according to UL 498.</p> <p>JET certification:</p> <p>Both versions are JET certified.</p>
What are the mechanical differences to the current version NAC3*X-W-TOP?	<p>The whole cable entry section had to be redesigned in order to:</p> <ul style="list-style-type: none"><li>- To cover the large cable range (10 - 16mm)</li><li>- To meet the standards requirement to prevent disassembling by hand</li><li>- To improve the assembly process</li></ul> <p>The housing and insert parts are the same</p>
When is the IEC 60799 relevant?	<p>This standard applies for "Cord Sets And Interconnection Cord Sets" and therefore covers cables to the mains and cables acting as power interconnections.</p>
Why is the bushing loose in one direction?	<p>This is to meet the standards requirement to prevent disassembling by hand. In order to open the cable entry a special tool will be required.</p>

## Technical Information

Product	
Title	NAC3FX-W-TOP-L
Connector series	powerCON TRUE1 TOP

**Electrical**

Dielectric strength	2.8 kVac
Insulation resistance	> 0.1 GΩ
Number of electronical contacts	2 + PE
Rating Europe	IEC EN 60320-1: 16 A 250 V AC
	Certified with cable types: H07RN-F3G2.5
Rating USA	UL 60320-1 & C22.2 No. 60320-1:19: 20 A 250 V AC
	Certified with cable types:
	- SOOW 12/3, SOOW 14/3
	- SJOOW 12/3

**Mechanical**

Cable O.D.	10 – 16 mm (0.39 – 0.63 inches)
Lifetime	Typically 5'000 mating cycles
Wire size (mm <sup>2</sup> )	2.5 mm <sup>2</sup>
Wire size (AWG)	14 – 12 AWG

**Material**

Contact plating	2 µm Ag
Contacts	Bronze (CuSn0.2)
Insert	Polyamide (PA 6.6 30 % GR)
Locking element	ZuAl4Cu1
Shell	Polyamide (PA 6.6 30 % GR)
Strain relief	Polyacetal (POM)

Environmental	
Flammability	UL 94 V-0
Protection class	IP65, UL50E enclosure type 4 (mated)
Temperature range	-30 °C to +80 °C